



TECHNICAL SPECIFICATIONS

MATERIALS:

- 15MM RIGA FORM BIRCH PLY
- HIGH DENSITY CLOSED CELL FOAM
- COARSE RESILIENT ANTI SLIP MATERIAL
- METAL SCREW CUPS

THE WIDEBOYZ CRACK VOLUMES USE A HIGH QUALITY 15MM RIGA FORM BIRCH PLY PRODUCT THAT GIVES AN EXCELLENT QUALITY FINISH, ARE HARD WEARING AND WITH A UNIQUE CONSTRUCTION DESIGN PROVIDE A STRONG AND RESILIENT PRODUCT. THE COMBINED USE OF A HIGH DENSITY CLOSED CELL FOAM AND A SPECIAL ANTI-SLIP MATERIAL PROVIDE HIGH LEVELS OF CoF (COEFFICIENT OF FRICTION) TO GIVE A UNIQUE JAMMING/CLIMBING EXPERIENCE.

FIXING:

ALL VOLUMES ARE FITTED WITH 12 SCREW PLACEMENTS EACH FITTED WITH A SPECIAL METAL SCREW CUP TO PROVIDE A SOLID FIXING AND ENHANCED LIFE TO THE PRODUCT. WE RECOMMENDED THAT ALL SCREW PLACEMENTS ARE USED WITH FULLY THREADED M5 WOOD SCREWS. MAKE SURE THAT THE CORRECT LENGTH OF SCREW IS USED SO AS AT LEAST 10MM IS PROTRUDING FROM THE BACK OF 18MM PLY. AVOID USING EXISTING HOLES IN THE PLYWOOD WHEN FIXING TO THE WALL AND THAT THE WALL IS A MINIMUM OF 18MM HARDWOOD PLY.

ALL SURFACES SHOULD BE FLAT TO PROVIDE A SOLID FIXING, UNEVEN SURFACES WILL DAMAGE THE BACK BOARD AND NOT GIVE AN EVEN FIXING TO THE WALL.

A FULL RISK ASSESSMENT BASED ON THE SPECIFIC WALL SURFACE SHOULD BE CARRIED OUT TO DETERMINE THE LIKELIHOOD AND IMPLICATIONS OF THE VOLUME MOVING AND NECESSARY ACTION TAKEN.

USE:

- THE USE AND SETTING OF THE VOLUMES MUST BE MADE BY COMPETENT PERSONS.
- YOU MUST CHECK AND BE AWARE OF THE QUALITY OF THE SUPPORTING WALL.
- THE VOLUMES MUST BE SET ON PLANE SURFACES.
- CHECK THE CRACK VOLUME AFTER ROUTE SETTING, AND THAT IT IS SECURE TO THE WALL
- NO ADDITIONAL SCREW ON HOLDS ARE TO BE FIXED TO THE VOLUME
- DURING THE SETTING, MAKE SURE THAT THE POSITIONING DOES NOT INCITE TO CERTAIN DANGEROUS MOVES.
- THE CRACK VOLUMES MUST BE SET AS TO AVOID ANY INJURY'S TO THE CLIMBER IN CASE OF FALL.
- THE CRACK VOLUMES SHOULD NOT INTERFERE WITH THE ROPE, FOR ITS SMOOTH RUNNING.
- CLEANING OF THE VOLUMES SHOULD BE DONE WITH A DAMP CLOTH, NO JET WASHING!

THE BUYER IS RESPONSIBLE FOR THE FIXING AND SETTING AND THE GOOD USE OF OUR CRACK VOLUMES. THEY MUST MAKE SURE THAT THE USE IS THE ONE FOR WHICH OUR PRODUCTS WERE CONCEIVED. THE MANUFACTURER WILL ACCEPT NO RESPONSIBILITY FOR HOWEVER MUCH DAMAGE THERE IS IN THE CASE OF THE NON-COMPLIANCE WITH THE INSTRUCTIONS OF USE DESCRIBED ABOVE.

HAND BUILT IN THE UK.